



Features

- CPU Speed 48 Mhz
- Program Memory 24 KB
- Data EEPROM 256 bytes
- 1 USB 2.0 12Mbit/s
- 1 Centronics 150kbit/s
- Power +5 V over USB
- Wide Operating Temperature: -20-60°C
- Low Profile, Low Power and Stylish Design

1 LPT

1 USB

Wide Temp.

Specifications

I/O

CENTRONICS	1x36 PIN Female
USB	1x36 PIN Female

Print File Format

PCL	PCL 3GUI
PCL	PCL 3
PCL	PCL 4
PCL	PCL 5
PCL	PCL 6

Convert to Captured Data

IMAGE	BMP
IMAGE	JPG
IMAGE	TIFF
DOCUMENT	PDF
DOCUMENT	TXT
MEDICAL	DICOM

Supported Software

STANDART	EasyCon
EXTENDED	BIZCON

Supported OS

WINDOWS	XP
WINDOWS	VISTA
WINDOWS	7
WINDOWS	SERVER 2003
WINDOWS	SERVER 2008

Printer Driver

HP	Laser Jet Series II
HP	Laser Jet 4
HP	Laser Jet 5
HP	Color Laser Jet 4500 PCL 5
HP	Color Laser Jet 8550 PCL
HP	Color Laser Jet 9500 PCL 5

Mechanical & Environmental

Color	Front Silver & Rear Silver
Power Input	5V DC
Power Type	USB Powerd
Operating Temp.	-20 - 60°C (-4 - 140°F)
Operating Humidity	5% - 90% Relative Humidity, Non-Condensing
Dimensions	112mm x 110mm x 30mm
Weight	195 gs

Distributed by:



www.print2usb.info

Ordering Information

Print2USB

PCL Converter Box